

## **EU-TYPE EXAMINATION CERTIFICATE**



The following model of Personal Protective Equipment has been subjected to an EU-type examination in accordance with the module B of the PPE regulation (2016/425) and has been shown to satisfy to essential health and safety requirements.

Certificate N° 0075/154/161/06/20/1847

Issued by CTC, Notified Body N°0075, to the following model of personal protective equipment :

Manufacturer: AIGLE INTERNATIONAL S.A

57 BOULEVARD DE MONTMORENCY,75016 PARIS

FRANCE

**Description** 

PPE Type: a safety and ESD control footwear

Product reference : SOLTER S3

Article code : T3051, T3052, T3053, T3131

Construction and material of outsole : Cement, EVA/Rubber Sole

**Pictures:** 



AIGLE

= PR = 57 BD DE MONTMORENCY 75016 PARIS

EUR UK US CN mm

42 8 81/2 260(3.0)

REF: T3051 - SOLTER \$3
EN ISO 20345: 2011
\$33 - SRC
ESD footwear EN 61340-5-1:2016
20/5/2020
FABRIQUE EN CHINE / MADE IN CHINA
TS9468 05.20 / T3051

T3053 T3131

In application of the Regulation 2016/425 of the European parliament and the Council of 9th March 2016 related to Personal Protective

Equipment and repealing the Directive 89/686/EEC.

Reference standard: EN ISO 20345: 2011 and EN 61340-5-1:2016

Classification: I Category: S3 SRC

Size range: 35-48 Slip resistance: SRC

Toecap nature: Non Metallic Insert nature: Non Metallic

At the date of certificate the product is in compliance with Annex XVII of REACh regulation (n° 1907/2006 and revisions)

Full description of the PPE, reference rules verified in the context of the EU-type examination and information given on the product are detailed in the manufacturer's technical file index 01 dated from JUNE. 2020

NOTA: Any modification to new items of the personal protective equipment object of this EU type approval certificate or any modification of the information contained in the manufacturer technical file which served for the deliverance of the EU type approval certificate (change of address, change of company status) should be brought to the attention of the notified body in accordance with Annex V §7.2 of Regulation 2016/425. Any marking on the PPE which is not concerned by the Regulation (UE) 2016/425, is not covered by this certificate

Issued in Lyon by

Maxence DREVET

MARKING

**Project Certification Manager** 

Date of first issue: 24 June 2020 End of validity date: 24 June 2025





www.ctcgroupe.com

cemarking@ctcgroupe.com

CTC - 4, rue Hermann Frenkel - 69367 Lyon cedex 07 - France Tél. : +33 (0)4 72 76 10 10 - Fax : +33 (0)4 72 76 10 00 - ctclyon@ctcgroupe.com



## **AIGLE INTERNATIONAL S.A**

# **MANUFACTURER'S TECHNICAL FILE**

**Reference of the product :** SOLTER S3

**Article code :** T3051, T3052, T3053, T3131

Technical file index: 01

Last update: JUNE, 2020

## **IDENTIFICATION**

Reference of the product: SOLTER S3

Article Code : T3051, T3052, T3053, T3131

Basic model

Technical file index: 01

Last update : JUNE, 2020

### Manufacturer:

## AIGLE INTERNATIONAL S.A

## 57 BOULEVARD DE MONTMORENCY,75016 PARIS

### **FRANCE**

tel: 33 (0)1 41 22 61 67

fax: N.A

### Factory:

ZHEJIANG ANKANG SAFETY EQUIPMENT CO.,LTD

1206, HONGYUAN ROAD, RUIAN CITY, ZHEJIANG PROVINCE

#### **CHINA**

Tel: 86 577-58901663 Fax: 86 577-58901660

## **FOOTWEAR DESCRIPTION**

## Footwear description:

The classification of this footwear is: I : Footwear made from leather and other materials, excluding all-rubber or all-polymeric footwear

The design of this footwear is: A: low shoe

## Visual description:

#### General view:



Outsole view:



Reference of the mould: 1703#

## Range of sizes:

35-48

## **Construction and material of outsole:**

Cement, EVA/Rubber Sole

## Field of use

Building site, Gas station, Decoration site

Risk assessment (Essential Health and Safety Requirement. Annex II - PPE Regulation)							
		Applicable	Covered by				
			✓	Standard			
§1	Requirements defined in the Annex II §1 are applicable to all PPE	<b>✓</b>	✓	Instruction for use			
	to all PPE		✓	Marking			
				Standard			
§1.4	Manufacturer's instructions and information is available	<b>✓</b>	<b>✓</b>	Instruction for use			
				Marking			
	PPE is designed and manufactured in a way that		✓	Standard			
§2.2	perspiration resulting from use is minimised. Otherwise	7	<u></u>	Instruction for use			
	it must be equipped with means of absorbing						
	perspiration.			Marking			
	If it is known that the design performance of new PPE		<b>✓</b>	Standard			
	may be significantly affected by ageing, the month and	✓					
<b>§2.4</b>	year of manufacture and/or, if possible, the month and year of obsolescence must be indelibly and		✓	Instruction for use			
	unambiguously marked on each item of PPE placed on						
	the market and on its packaging.		✓	Marking			
			<u></u>	Standard			
§2.6	PPE is intended for use in potentially explosive atmospheres	<b>V</b>	<u> </u>	Instruction for use			
92.0		Ŭ		Marking			
		7	<u> </u>	Standard			
§2.9	PPE incorporating components which can be adjusted or		<u> </u>	Instruction for use			
32.0	removed by the user			Marking			
	PPE bearing one or more identification markings or	<b>V</b>		_			
§2.12	indicators directly or indirectly relating to health and			Instruction for use			
	safety		Standard				
	·		<u> </u>	Standard			
§2.14	Multi-risk PPE	<b>✓</b>	<u> </u>	Instruction for use			
			<u> </u>	Marking			
	The PPE is intended to protect against impact caused by		<u> </u>	Standard			
§3.1.1	falling or ejected objects and collisions of parts of the	<b>✓</b>	<u> </u>	Instruction for use			
	body with an obstacle		<u> </u>	Marking			
	The PPE is intended to protect against falls due to slipping	7	✓	Standard			
§3.1.2.1			<b>✓</b>	Instruction for use			
			✓	Marking			
	The PPE is intended to protect against static compression of a part of the body	7	✓	Standard			
§3.2			<b>✓</b>	Instruction for use			
	compression of a part of the body		<b>✓</b>	Marking			
	The DDF is intended to make the control of the cont		<b>✓</b>	Standard			
§3.3	The PPE is intended to protect against mechanical injuries	<b>✓</b>	<b>✓</b>	Instruction for use			
	injuries			Marking			

## **FOOTWEAR CONSTITUTION**

	Ref	Material	Color
UPPER	AK-U01	Microfiber PU	Black/dk.brown, black/grey/dk.grey, black, black/dk.grey
	AK-U02	counter:TPU	black/yellow
COLLAR	AK-U01	Microfiber PU	Dk.brown, grey/dk.grey, black, dk.grey
TONGUE	AK-U01	Microfiber PU	Dk.brown, grey, black, dk.grey
VAMP LINING	AK-L01	Mesh	Black
QUARTER LINING	AK-L01	Mesh	Black, yellow, black, peach
INSOCK	AK-ISK01	Black Mesh with dk.grey EVA foam, full removable	Black/dk.grey
OUTSOLE	1703#	EVA+Rubber	Black,black, black, dk.grey/black
INSOLE	501	MINGRUIJIA Non-metallic Anti- penetration insole	White/Blue
TOE CAP	604A	MANJOY Composite toecap	Beige
INSERT	501	MINGRUIJIA Non-metallic Anti- penetration insole	White/Blue
		tongue: TPU with logo	Black/yellow
DECORATIVE ELEMENTS		Collar: webbing loop	Black
		Upper: Plastic eyelets	Black

## **PROTECTION SCOPE**

## **Basic requirements:**

This product has been designed to be a safety and ESD control footwear.

The technical rules are:

European Standard EN ISO 20344: 2011 Personal protective equipment - test methods for footwear

European Standard EN ISO 20345: 2011: Personal protective equipement - Safety footwear

EN 61340-5-1:2016

It is a category II product

Requirement of the standard EN ISO 20345: 2011 concerning the value of the coefficient of friction of ceramic tiles floor with detergent solution and steel floor with glycerol (SRC)

Requirement of the paragraph 5.8.1. Design of the standard EN ISO 20345: 2011 concerning cleated outsole.

At the date of certificate, the product is in compliance with Annex XVII of European REACh regulation (n° 1907/2006 and revisions)

#### Additional requirements:

The additional requirements are:


- Closed seat region
- Antistatic footwear
- Energy absorption of seat region
- Fuel oil resistance
- Upper : Water penetration and water absorption
- Penetration resistance

## **MARKING - PACKAGING**

### Information printed on the footwear:

- \* Logo of the authorized representative
- \* Logo (€
- \* Manufacturer's type designation
- \* Postal address of manufacturer
- \* Footwear's reference SOLTER S3
- \* Article code T3051, T3052, T3053, T3131
- \* Size
- \* Year of manufacture and at least quarter
- \* The number and year of the Standard used
- \* The symbol(s) of the additional requirements

### Marking example:



The location of marking is: back side of tongue

### Method of marking on the footwear:

stitching on back side of tongue

## Packaging:

One pair of shoes packed with tissued paper in inner box

# References of test reports performed in order to verify the compliance with the requirements of the technical rules :

Laboratory	References	Laboratory	References	
СТС	D191225263_1	СТС	D200609091_1	
CTC	D200404850_1	Intertek	GZHT90775033	
CTC	D200403925_1	Intertek	GZHT90790922	
CTC	D200404842_1	Intertek	GZHT90601628	
CTC	D200100526_1	Intertek	GZHT90809768	
CTC	D200404841_1	Intertek	GZHT90765908	
CTC	D200101501_1	Intertek	GZHT90738287	
CTC	D191225213_1	Intertek	GZHT90808459	
CTC	D200101502_1	Intertek	GZHT90904086	
СТС	D200505981_1	Intertek	GZHT90820844	

## **MEANS OF CONTROL**

Generally we control the quality of our safety footwear as follows:

1/ we will test some important items, such as impact, compression, slip resistance during development of products. After all properties can meet the requirement, then we will put them into mass production; 2/ We will ask our raw material supplier to provide us good reports, for example, steel toecaps, we need good report for impact, compression; penetration resistance insert, we need report for penetration and flex resistance; and for leather we need report for tear strength, tensile strength, WVP and Cr VI. All report must be in accordance with correct standard, such as EN12568:2010 for toecaps and insert; EN ISO 20345:2011 for upper material. 3/ Our QC will make sure that the quality check must be performed strictly for each step. From cutting, stitching, lasting, injection and cleaning, if some problems are found, we must solve them at once in order that the good quality shoes can be produced smoothly;

4/ We will pick up some finished shoes from warehouse at random, and send them to testing company to perform impact, sole flex resistance and abrasion resistance, bonding strength per each Batch.

5/ Before shipment, we will ask our QC to carry out final inspection randomly. The whole goods can be delivered when the result of inspection is positive.

## PPE subject to ageing :

Peremption period: 3 years when stored in appropriate conditions (humidity, temperature, clean, ventilated, light). Before use, the footwear shall be visually controlled, in case of deterioration the footwear must be scrapped (abrasion, cut, tear, ...).

## Declaration of conformity:

Available on: http://www.anklle.com/jcxg/qt/index.html